

ガソリン乗用車・RV車

通称名	型式	原動機		変速装置の型式及び変速段数	エネルギー消費効率 (km/L)	1km走行におけるCO2排出量 (g-CO2/km)	車両重量 (kg)	主要燃費向上対策	その他エネルギー消費効率の異なる要因			(参考) 低排出ガス認定レベル
		型式	総排気量 (L)						主要排出ガス対策	駆動形式	その他	
ホクスター	GH-98623	23	2.687	5MT	9.4	247.0	1340~1370	V	3W+AS	R		
	GH-98623	23	2.687	5AT(LTC)	8.3	279.7	1370~1400	V	3W+AS	R		
ホクスター S	GH-98624	24	3.179	6MT	8.5	273.1	1370~1400	V	3W+AS	R		
	GH-98624	24	3.179	5AT(LTC)	7.8	297.6	1400~1430	V	3W+AS	R		
911カラ	GH-99603S	03S	3.595	6MT	7.6	305.5	1420	V	3W+AS	R		
	GH-99603	03	3.595	6MT	7.5	309.6	1420	V	3W+AS	R		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1470	V	3W+AS	R		
	GH-99705	05	3.595	6MT	8.1	286.6	1440	V	3W	R		
	GH-99705	05	3.595	5AT(LTC)	7.5	309.6	1480	V	3W	R		
911カラS	GH-997M9701	M9701	3.824	6MT	7.8	297.6	1460	V	3W	R		
	GH-997M9701	M9701	3.824	5AT(LTC)	7.2	322.5	1500	V	3W	R		
911カラ カブリオ	GH-99603	03	3.595	6MT	7.5	309.6	1510	V	3W+AS	R		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1560	V	3W+AS	R		
911タルガ	GH-99603	03	3.595	6MT	7.5	309.6	1500	V	3W+AS	R		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1550	V	3W+AS	R		
911カラ 4	GH-99603S	03S	3.595	6MT	7.6	305.5	1460	V	3W+AS	A		
	GH-99603	03	3.595	6MT	7.5	309.6	1460	V	3W+AS	A		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1510	V	3W+AS	A		
911カラ 4 カブリオ	GH-99603S	03S	3.595	6MT	7.6	305.5	1550	V	3W+AS	A		
	GH-99603	03	3.595	6MT	7.5	309.6	1550	V	3W+AS	A		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1600	V	3W+AS	A		
911カラ 4S	GH-99603S	03S	3.595	6MT	7.6	305.5	1520	V	3W+AS	A		
	GH-99603	03	3.595	6MT	7.5	309.6	1520	V	3W+AS	A		
	GH-99603	03	3.595	5AT(LTC)	7.0	331.7	1570	V	3W+AS	A		
カイエン	GH-9PABFD	BFD	3.188	6AT(LTC)	6.9	336.5	2270-2370	V	3W+AS	A		
	GH-9PABFD	BFD	3.188	6MT	7.3	318.0	2250	V	3W+AS	A	類別0017	
	GH-9PABFD	BFD	3.188	6MT	7.3	318.0	2270-2350	V	3W+AS	A	類別0017を除くMT車	
	GH-9PABFDA	BFD	3.188	6AT(LTC)	6.9	336.5	2300-2400	V	3W+AS	A		
	GH-9PABFDA	BFD	3.188	6MT	7.3	318.0	2280-2380	V	3W+AS	A		
カイエンS	GH-9PA00	00	4.510	6AT(LTC)	5.8	400.3	2420-2520	V	3W+AS	A		
	GH-9PA00	00	4.510	6MT	6.1	380.6	2380-2480	V	3W+AS	A		
	GH-9PA00A	00	4.510	6AT(LTC)	5.8	400.3	2450-2550	V	3W+AS	A		
	GH-9PA00A	00	4.510	6MT	6.1	380.6	2410-2510	V	3W+AS	A		
カイエンターボ	GH-9PA50A	50	4.510	6AT(LTC)	5.5	422.1	2480-2580	V	3W+AS	A		